Digimerge | Right for Business DH200+ Series Digital Video Surveillance

Recorder 4/8/16 Channel CMS-DH PC/Mac 3G Mobile 480/240fps







Features

- H.264 compression, supports D1 resolution video recording
- Lite Touch operation
- 3G Smart phone and tablet view, supports BlackBerry, iPhone, iPad and Android
- Fully compatible with both PC and Mac
- CMS-DH application supports up to 300 DVRs, 64 channels, live-playback, E-map, full control, up to 8 screen display
- 480fps 'real-time' viewing, 240fps recording (8/16 channel)
- Excellent quality live and recorded video and audio
- Back-up through USB port to Flash and optical drives
- Security Certified Hard Disk with up to 2TB of data storage
- Free DDNS by Digimerge



3G Smart
Phone Viewing,
BlackBerry,
iPhone, iPad
& Android





GUI CMS-DH

Specifications

Video inputs	4/8/16 x 1.0Vp-p, CVBS, 75ohms, BNC
Video outputs	1 composite (BNC) 1 spot output, programmable 1 VGA
Audio inputs	1 x line-in, RCA
Audio output	1 x line-out, RCA
Audio	1-way audio conference (via network)
Video Compression	H.264 hardware codec
Audio compression	G.711
Supply voltage	100VAC - 240VAC, 12VDC, 3A, 50/60Hz
Power consumption:	Approx. 19.2 watts (HDD 250GB)
Operating Temp. Range	32°~104° F / 0° ~ 40° C
Hard disk capacity	1 HDD (Max 2TB), 100% duty cycle
Operating System	Linux (embedded)
OSD Navigation	USB mouse, IR controller or 20 key front panel
Backup	Via USB to Flash & optical drives*
Back-up file formats	Embedded player/Convertible to AV
Recording resolution	360 x 240 : 240/200 (NTSC/PAL) 720 x 240 : 120/100 (NTSC/PAL) 720 x 480 : 60/50 (NTSC/PAL)
Image size	5-30 KB (720 x 480, 720 x 576) FPS 3-19 KB (720 x 240, 720 x 288) FPS 2-12 KB (360 x 240, 360 x 288) FPS
Record Scheduling	Daily, Weekly adjust specific Hr per channel
Pre/Post alarm recording	5 seconds (Pre); 5 minutes (Post), programmable per camera
Event/Log search	For user login/out, configuration changes, remote access, connects/disconnects
Playback:	Single, Quad, 8, 16 CH Simultaneous
Alarm inputs	4/8/16 x TTL, programmable as NC/NO
Alarm outputs:	1 x Relay with NO/NC contact; 24VDC/2A, 240VAC/2A resistive
Activity detection	4x4 grid (SET)/ 28 x 24grid (CLIENT S/W)/ Sensitivity levels: 20
PTZ Control	RS-485/RS-422 Interface
Mobile Viewing	3G Smart Phone viewing, supports BlackBerry, iPhone & Android*
Front Key:	Max 20 (Touch Sensor)
Front LED	Power, REC, HDD
Unit Weight	1.91 kg/4.2 Lb
Unit Dimensions	11.0" / 280mm 12.7"/315mm 2.2"/55mm (W x D x H)
Carton Weight:	3.16 kg/6.8 lbs
Carton Dimensions	13.4" /340mm 5.7"/145mm 16.14"/410mm (W x D x H)
Networking	

Networking

Live View, Live Recording, Search, Set-up, Back-up **Remote Functions Network Speed Control** 8 levels (64KB ~ 8MB)/sec **Network Protocol** TCP/IP, DDNS and Web **Network Interface** 10/100-Base-TX, RJ-45

Digimerge Technologies Inc.


Dimensions


Weight: 3.16kg/6.8lbs

340mm x 145mm x 410mm / 13.4" x 5.7" x 16.1" Package

Dimensions: $(W \times H \times D)$

0.02 Cubic Metres / 0.71 Cubic Feet **Cube:**





Product Information

UPC: **DH204501** 4 Channel 500GB HDD 8-41430-00641-1 **DH2041TB** 4 Channel 1TB HDD 8-41430-00642-8 DH208501+ 8 Channel 500GB HDD 8-41430-00634-3 DH2081TB+8 Channel 1TB HDD 8-41430-00638-1 DH2082TB+ 8 Channel 2TB HDD 8-41430-00714-2 DH216501+ 16 Channel 500GB HDD 8-41430-00635-0 DH2161TB+ 16 Channel 1TB HDD 8-41430-00639-8 DH2162TB+ 16 Channel 2TB HDD 8-41430-00703-6

Includes: DVR, HDD Pre-Installed, Remote Control, Power

Supply, Software application CD